# REAMERS, RETHREADING, RIVETTING **SOLDERING TOOLS & TORCHES**



Rethreadi	ng Tools	.Page No. 41
	Rethreading Dies and Sets	
	Tap and Die Sets	
	Thread Restoring Files	
	Thread Chasers Internal and External	
	Tap Wrenches and Die Holders	
Solderina	Irons	Page No. 41
	Soldering Irons Gas	
	Soldering Irons Electric	
	Solder and Flux	
Reamers.	Jet and Tip Cleaners	Page No. 41
<b>,</b>	Tapered Reamers	
	Jet Drill Sets	
	Oxy Tip Cleaners	
Torches		Page No. 41
	UV Torches	
	Mechanics Torches	
	Bend A Light	
	Bright eyes	
Rivet and	Nut Set Rivetting Tools	Page No. 41
	Pop Rivet Guns and Rivets	
	Nut Set Rivet Guns and Nut Sets	••••••







# No.8001 **UNF/UNC Thread File**

#### • Fine & coarse threads

• 60 Degree pitch

Restores battered, rusted and corroded threads guickly. All the thread sizes are clearly marked on the file. Select the correct size thread, overlap the file a few good threads and use the tool just like a file to restore damaged area. Works on all diameters, right or left hand threads.

Thread sizes: 11, 12, 13, 14, 16, 18, 20, 24 tpi

Length: 8.1/2"(220mm) Width: 7/16"(11mm) Square

# No.8002 **UNF/UNC Thread File**

• Fine & coarse threads

• 60 Degree pitch

Restores battered, rusted and corroded threads quickly. All the thread sizes are clearly marked on the file. Select the correct size thread, overlap the file a few good threads and use the tool just like a file to restore damaged area. Works on all diameters, right or left hand threads.

Thread Sizes: 9, 10, 12, 16, 20, 27, 28, 32tpi

Length: 8.1/2"(220mm) Width: 7/16"(11mm) Square



# No.8008 **Metric Thread File**

#### • Fine & coarse threads

• 60 Degree pitch

Restores battered, rusted and corroded threads quickly. All the thread sizes are clearly marked on the file. Select the correct size thread, overlap the file a few good threads and use the tool just like a file to restore damaged area. Works on all diameters, right or left hand

Sizes: 1.0, 1.25, 1.5, 1.70.75,5, 2.00,2.5, 3.0mm pitch

Length: 8.1/2"(220mm) Width: 7/16"(11mm) Square





# No.8003 **Thread File Handle**

Plastisol handle fits thread files: #8001, #8002 and #8008 to protect hands when doing repetitive work.

# Internal ends of file

No.8006

60 Degree Pitch

can be used as a thread gauge!

Internal & External Thread File UNF / UNC

Restores battered, rusted and corroded threads quickly. All the thread sizes are clearly marked on the file. Select the correct size thread, overlap the file on a few good threads and use the tool just like a file to restore damaged area. Works on all diameters, right or left hand threads.

Fine & Coarse Thread Sizes: 10, 11, 12, 14, 16, 18, 20 & 24 tpi Length: 9"(230mm) Width: 7/16"(11mm) Square

Internal ends of file can be used as a Internal & External thread gauge!

No.8012 **Thread File Metric** 

60 Degree Pitch

Restores battered, rusted and corroded threads quickly. All the thread sizes are clearly marked on the file. Select the correct size thread, overlap the file on a few good threads and use the tool just like a file to restore damaged area. Works on right or left hand threads.

Metric Fine & Coarse Thread Sizes:

0.8, 1, 1.25, 1.5, 1.75, 2.0 2.5 & 3.0mm pitch


Length: 9"(230mm) Width: 7/16"(11mm) Square



# No.8009 Universal 60° Thread File

A single blade 60° thread file that will renew threads on metric and imperial bolts and screws. Has cushion grip handle.

Length: 9"(230mm)



# No.8014 5Pc. Thread File Set

Restores battered, rusted and corroded threads quickly. Select the correct size thread, overlap the file on a few good threads and use the tool just like a file to restore damaged area. Works on all diameters, right or left hand threads.

Thread File Sizes:

#8001 - 11, 12, 13, 14, 16, 18, 20, 24 tpi #8002 - 9, 10, 12, 16, 20, 27, 28, 32 tpi #8008 -0.75,1.0,1.25,1.5,1.75,2.0, 2.5, 3mm Thread Gauges: #8031-SAE & #8033-Metric

# No.1774 Thread File For Pipe Thread Fittings

Restores battered, rusted and corroded threads quickly. All the thread sizes are clearly marked on the file. Select the correct size thread, overlap the file on a few good threads and use the tool just like a file to restore damaged area. Works on all diameters, right or left hand threads.

Pipe Thread Sizes: 8, 11.1/2, 14 and 18 tpi

Length: 8.1/2"(216mm) Width: 7/16"(11mm) Square





# No.8013 10Pc. UNC/UNF **Rethreader Dies**

- Actual nut size rethreader dies, will not undercut
- Reach into places where standard die nuts won't

Set of ten UNF & UNC rethreader dies, made of the highest quality carbon steel to exacting thread sizes.

Sizes: 1/4", 5/16", 3/8", 7/16" & 1/2" UNF 1/4", 5/16", 3/8", 7/16" & 1/2" UNC



## No.8010

### 8Pc. UNC Rethreader Dies

Contains: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16". 5/8". 3/4" UNC

	,		
Individual Sizes	;	Available	Separately

marviduai C	nzes Available deparately
Part No.	Description
8010-08	1/4" UNC Rethreader Die
8010-10	5/16" UNC Rethreader Die
8010-12	3/8" UNC Rethreader Die
8010-14	7/16" UNC Rethreader Die
8010-16	1/2" UNC Rethreader Die
8010-18	9/16" UNC Rethreader Die
8010-20	5/8" UNC Rethreader Die
8010-24	3/4" UNC Rethreader Die



### 8Pc. UNF Rethreader Dies

Contains: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 3/4" UNC

Individual Sizes Available Separately

mannaaa	7 Tranabio Coparatory
Part No.	Description
8011-08	1/4" UNF Rethreader Die
8011-10	5/16" UNF Rethreader Die
8011-12	3/8" UNF Rethreader Die
8011-14	7/16" UNF Rethreader Die
8011-16	1/2" UNF Rethreader Die
8011-18	9/16" UNF Rethreader Die
8011-20	5/8" UNF Rethreader Die
8011-24	3/4" UNF Rethreader Die



# No.8005 5Pc. Metric Rethreader Dies

**Sizes:** 6 x 1.0mm, 7 x 1.0mm, 8 x 1.25mm, 10 x 1.5mm, 12 x 1.75mm.

Individual Sizes		Available Separately
Part No.	Description	1
8017-6M	6 x 1.0mm	Metric Rethreader Die
8017-7M	7 x 1.0mm	Metric Rethreader Die
8017-8M	8 x 1.25mm	Metric Rethreader Die
8017-10MC	10 x 1.5mm	Metric Rethreader Die
8017-12MC	12 x 1.75mm	Metric Rethreader Die



## 7Pc. Metric Retheader Dies

Sizes: 6 x 1.0mm, 8 x 1.25mm, 10 x 1.25mm, 10 x 1.5mm, 12 x 1.25mm 12 x 1.5mm 12 x 1.75mm.

Individual Sizes Available Separately

Part No.	Description	1		
8017-6M	6 x 1.0mm	Metric	Rethreader	Die
8017-8M	8 x 1.25mm	Metric	Rethreader	Die
8017-10MM	10 x 1.25mm	Metric	Rethreader	Die
8017-10MC	10 x 1.5mm	Metric	Rethreader	Die
8017-12MF	12 x 1.25mm	Metric	Rethreader	Die
8017-12MM	12 x 1.5mm	Metric	Rethreader	Die
8017-12MC	12 x 1.75mm	Metric	Rethreader	Die



# No.8024 8Pc. Flared Tube Fitting Rethreader Set

Set includes the following sizes:

*Taps:*1/2" x 20tpi, 7/16" x 24tpi (Tube Threads) 3/8" x 24tpi, 1/8" x 27npt (Tube Threads)

Dies: 1/2" x 20tpi, 7/16" x 24tpi(Tube Threads) 3/8" x 24tpi, 1/8" x 27npt (Tube Threads)

Part No.	Description	
8024-04T	1/8" x 27npt	Tap (Tube Thread)
8024-12T	3/8" x 24tpi	Tap (Tube Thread)
8024-14T	7/16" x 24tpi	Tap (Tube Thread)
8024-16T	1/2" x 20tpi	Tap (Tube Thread)
8024-04D	1/8" x 27npt	Die (Tube Thread)
8024-12D	3/8" x 24tpi	Die (Tube Thread)
8024-14D	7/16" x 24tpi	Die (Tube Thread)
8024-16D	1/2" x 20tpi	Die (Tube Thread)



### No.8015

# 5Pc. UNF Large Rethreader Dies

Contains: 3/4", 7/8", 1", 1.1/8" & 1.1/4"UNF Individual Sizes Available Separately

Part No.	Description	
8015-24	3/4" UNF Rethreader Die	
8015-28	7/8" UNF Rethreader Die	
8015-32	1" UNF Rethreader Die	
8015-36	1.1/8" UNF Rethreader Die	
8015-40	1 1/4" UNF Rethreader Die	



# No.J7520

# 3/4" x 20tpi Armature Die Nut

Special size re-threader die nut for repairing damaged threads on many alternator armatures.

Size: 3/4" x 20tpi



# No.8016 5Pc. UNC Large Rethreader Dies

Contains: 3/4", 7/8", 1", 1.1/8" & 1.1/4"UNC Individual Sizes Available Separately

Part No.	Description
8016-24	3/4" UNC Rethreader Die
8016-28	7/8" UNC Rethreader Die
8016-32	1" UNC Rethreader Die
8016-36	1.1/8" UNC Rethreader Die
2016-40	1 1/4" LINC Rethreader Die





# No.TC6 6Pc. National Coarse RethreaderTap Set

Sizes: 1/4" x 20, 5/16" x 18, 3/8" x 16, 7/16" x 14, 1/2" x 13, 9/16" x 12

3, 1/4"-20,

1/4"-20,

ıps, will

ndard

.25mm,

reader taps

Part No.	Description	
TC6-08	1/4" x 20	Rethreader Tap
TC6-10	5/16" x 18	Rethreader Tap
TC6-12	3/8" x 16	Rethreader Tap
TC6-14	7/16" x 14	Rethreader Tap
TC6-16	1/2" x 13	Rethreader Tap
TC6-18	9/16" x 12	Rethreader Tap



# 6Pc. National Fine **Rethreader Tap Set**

Sizes: 1/4" x 20, 5/16" x 18, 3/8" x 16, 7/16" x 14, 1/2" x 13, 9/16" x 12

Part No.	Description		
TF6-08	1/4" x 20	Rethreader Tap	
TF6-10	5/16" x 18	Rethreader Tap	
TF6-12	3/8" x 16	Rethreader Tap	
TF6-14	7/16" x 14	Rethreader Tap	
TF6-16	1/2" x 13	Rethreader Tap	
TF6-18	9/16" x 12	Rethreader Tap	



# No.TM7 7Pc. Metric Retheader Tap Set

Part No.	Description
TM7-6M	6 x 1.0mm Metric Rethreader Tap
TM7-8M	8 x 1.25mm Metric Rethreader Tap
<b>TM7-10MF</b>	10 x 1.25mm Metric Rethreader Tap
TM7-10MC	10 x 1.5mm Metric Rethreader Tap
TM7-12MF	12 x 1.25mm Metric Rethreader Tap
TM7-12MM	12 x 1.5mm Metric Rethreader Tap
TM7-12MC	12 x 1.75mm Metric Rethreader Tap



Restore damaged internal pipe threads easily with this universal tool. Supplied with 3 popular die sets.

- 1: 14tpi for 3/4"Pipe 2: 11.5tpi for 1" to 2"Pipe 3: 8tpi for up to 6"Pipe
- Capacity: 3/4" to 6"(19 to 150mm) Diameter



# No.8004-A Imperial Die Set

Replacement imperial die set for use with T&E No.8004 Internal Rethreader.

Sizes: 8, 9, 10, 11, 11.5, 12, 13, 14, 16, 18, 20, 24, 27, 28, 32tpi



## No.8004-M **Metric Die Set**

Replacement imperial die set for use with T&E No.8004 Internal Rethreader.

Sizes: 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0mm pitch



No.TM8

**8PC. Metric Rethreader Taps** 

& Die Set

Contains eight Metric Dies and Taps to

FT-290 contains one each dies and taps

supplement old TRCOMBO.

# No.8070 Internal / External Metric **FWD Thread Chaser Set**

New design for both internal and external front wheel drive spindle thread repair. Use with a deep socket or the tommy bar supplied. Includes: #8071 thru #8079 as listed in table.



Individual Sizes:

(Available Separately)

IIIuiviuuai Si	263. (Available Separately)
Part No.	Description
8071	M14 x 1.5 Thread Chaser
8072	M16 x 1.5 Thread Chaser
8073	M18 x 1.5 Thread Chaser
8074	M20 x 1.5 Thread Chaser
8075	M22 x 1.5 Thread Chaser
8076	M24 x 1.5 Thread Chaser
8078	M27 x 2.0 Thread Chaser
8079	M28 x 1.5 Thread Chaser
8081	5/8" UNF Thread Chaser
8082	3/4" UNF Thread Chaser
8083	7/8" UNF Thread Chaser
8084	1" UNF Thread Chaser
8085	1.1/16" UNF Thread Chaser
8086	Tommy Bar



# No.8080 Internal / External SAE **FWD Thread Chaser**

New design for both internal and external front wheel drive spindle thread repair. Use with a deep socket or the tommy bar supplied. Includes: #8081 thru #8085 as listed in table.

## RETHREADING TOOLS





# No.J7402 **Universal Outside Thread Chaser**

- Capacity: 1.1/4" to 5"(30 to 130mm)
- Includes metric and imperial dies

Tighten the tool slightly on the good threads then back it off over the damaged thread area to restore threads quickly & accurately. Die cast alloy "V" pad that will not damage the threads. *Die sizes:* 4, 5, 6, 7, 7.5, 8, 9, 10, 11, 11.5, 12, 14, 16, 18, 20 & 24tpi

1.0mm, 1.25mm, 1.5mm, 1.75mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm pitch



- Capacity: 5/32" to 1.1/2"(4 to 38mm)
- 55° Angle HSS blades HRC62 Hardness

Tighten the tool slightly on the good threads then back it off over the damaged thread area to restore threads quickly & accurately. Mini size enables use in confined areas. Will work on all types of threads with diameters of 5/32" to 1.1/2" (4 to 38mm).



### No.7403

# Replacement Die Set

Replacement imperial die set for use with T&E No.J7402 replacement die set.

Metric Sizes:

1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0, 3.5 & 4.0mm pitch

Imperial Sizes:

4, 5, 6, 7, 7.5, 8, 9, 10, 11, 11.5, 12, 14, 16, 18, 20 & 24tpi



# **Universal Thread** & Size Gauge Set

Gauge allows quick identification of thread pitch or threads per inch. One tool identifies both thread diameter & pitch. Handy drill / tap chart included. Identifies the following thread sizes:

1.Imperial thread sizes:

1/4" to 3/4" (10 to 28tpi)

2.Metric thread sizes:

2.5 to 22mm (0.45 to 2.5mm pitch)

3. Pipe thread sizes:

1/16" to 1/2" with 14 to 27tpi

4. Spark plug thread sizes: 10mm, 12mm, 14mm & 18mm

# No.6432 **Nut & Bolt Gauge**

Easy to read gauge makes precise measurements of nut and bolt diameters, screw length etc. Made of ABS plastic with white print on black back ground for easy readings.

Range: 1/4" to 3/4" 6mm to 20mm 6 Gauge to 10 Gauge



# No.8031 **SAE Screw Pitch Gauge**

(60° Thread)

Inexpensive gauges include individual blades to determine degree of thread and threads per inch or pitch in millimetres.

29 Blades. Range:

4 to 42tpi 60 degree threads.



# No.8032 **Whitworth Screw Pitch Gauge** (55° Thread)

Inexpensive gauges include individual blades to determine degree of thread and threads per inch or pitch in millimetres. 28 Blades. Range: 18 to 62 Gauge.

BSP & BSF threads are also 55 Degrees.



# No.8033 **Metric Screw Pitch Gauge** (60° Thread)

Inexpensive gauges include individual blades to determine degree of thread and threads per inch or pitch in millimetres. 24 Blades, Range:

0.25 to 6.00 pitch (ISO Metric)

## RETHREADING TOOLS





# No.8021 18Pc. UNF & UNC Rethreader Set

Contains eight UNF & eight UNC rethreader dies with two thread files for restoring external threads.

**Die Sizes:** 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 3/4"UNF 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 3/4"UNC

File Sizes: 9, 10, 11, 12, 13, 14, 16, 18, 20, 24, 27, 28, 32tpi.



# No.8023 26Pc. UNF / UNC Retheader Set

Contains six UNF & UNC rethreader taps and seven UNF & UNC rethreader dies.

Rethreader Die Sizes: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8" UNC

1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8" UNF 1/4", 5/16", 3/8", 7/16", 1/2", 9/16" UNC

Rethreader Tap Sizes:

1/4", 5/16", 3/8", 7/16", 1/2",9/16" UNF

Supplied in blow mold case.



# No.6032 5Pc.Wheel Stud Rethreader Kit

Properly repairs and renews damaged threads on wheel studs found on most Australian, American, European & Asian cars and light trucks. Die Nut Sizes: 7/16" x 20, 1/2" x 20, 12 x 1.25mm, 12 x 1.5mm Thread File Sizes: 20tpi, 1.25mm, 1.5mm pitch



## No.8027 15Pc. Metric Rethreader Set

Contains fourteen metric rethreader taps and dies, with one metric thread files for restoring external threads.

#### One Metric Thread File:

0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0mm

#### Rethreader Die Sizes:

6x1.00, 8x1.25, 10x1.25, 10x1.50, 12x1.25, 12x1.5, 12x1.75mm Rethreader Tap Sizes:

6x1.00, 8x1.25, 10x1.25, 10x1.50, 12x1.25, 12x1.5, 12x1.75mm Supplied in blow mold case.



# No.8022 43Pc. UNF, UNC & Metric Rethreader Kit

Contains seven UNC, seven UNF and six Metric rethreader dies, six UNC, six UNF and six Metric rethreader taps, one UNF and UNC thread file and one metric thread file.

Rethreader Die Sizes:

1/4", 5/16", 3/8", 7/16", 1/2", 9/16" & 5/8" UNC 1/4", 5/16", 3/8", 7/16", 1/2", 9/16" & 5/8" UNF 6x1, 8x1.25, 10x1.5, 12x1.25, 12x1.5, 12x1.75mm

1/4", 5/16", 3/8", 7/16", 1/2" & 9/16" UNC 1/4", 5/16", 3/8", 7/16", 1/2" & 9/16" UNF Rethreader Tap Sizes:

6x1, 8x1.25, 10x1.5, 12x1.25, 12x1.5, 12x1.75mm





T45M 51Pc. Metric Stock & Die Set T45A 51Pc. NF/NC Stock & Die Set



T40M 40Pc. Metric Tap & Die Set



T40A 40Pc. SAE Tap & Die Set

## No.T45A

# 51Pc. SAE Tap & Die Set High grade alloy steel

<u>Taps</u>			
1/4" x 20NC	1/4" x 28NF	5/16" x 18NC	5/16" x 24NF
3/8" x 16NC	3/8" x 24NF	7/16" x 14NC	7/16" x 20NF
1/2" x 13NC	1/2" x 20NF	9/16" x 12NC	9/16" x 18NF
5/8" x 11NC	5/8" x 18NF	3/4" x 10NC	3/4" x 16NF
7/8" x 9NC	7/8" x 14NF	1" x 8NC	1" x 14NF
4 4/2!! OD C=!!4	Diag		

#### 1.1/2" OD Split Dies

5/8" x 11NC	5/8" x 18NF	_	J!4 4 4
1/2" x 13NC	1/2" x 20NF	9/16" x 12NC	9/16" x 18NF
3/8" x 16NC	3/8" x 24NF	7/16" x 14NC	7/16" x 20NF
1/4" x 20NC	1/4" x 28NF	5/16" x 18NC	5/16" x 24NF

To edit text

#### 2" OD Snlit Dies

- 0- 00000			
3/4" x 10NC	3/4" x 16NF	7/8" x 9NC	7/8" x 14NF
1" x 8NC	1" x 14NF		

"T" Style Tap Wrench / Bar Type Tap Wrench 2" Dia. Die Stock Wrench with a 1.1/2" Reducing Adaptor Stubby Screwdriver / Blow Mold Case

## No.T45M

# 51Pc. Metric Tap & Die Set High grade alloy steel

<u>Taps</u>			
6 x 0.75mm	6 x 1.0mm	8 x 1.25mm	8 x 1.5mm
10 x 1.25mm	10 x 1.5mm	12 x 1.5mm	12 x 1.75mm
14 x 1.5mm	14 x 2.0mm	16 x 1.5mm	16 x 2.0mm
18 x 1.5mm	18 x 2.5mm	20 x 1.5mm	20 x 2.5mm
22 x 1.5mm	22 x 2.5mm	24 x 1.5mm	24 x 3.0mm

#### 1.1/2"OD Split Dies

6 x 0.75mm	6 x 1.0mm	8 x 1.25mm	8 x 1.5mm
10 x 1.25mm	10 x 1.5mm	12 x 1.5mm	12 x 1.75mm
14 x 1.5mm	14 x 2.0mm	16 x 1.5mm	16 x 2.0mm
18 x 1 5mm	18 x 2.5mm		

#### 2"OD Split Dies

20 x 1.5mm	20 x 2.5mm	22 x 1.5mm	22 x 2.5mm
24 x 1.5mm	24 x 3.0mm		

"T" Style Tap Wrench / Bar Type Tap Wrench 2" Dia. Die Stock Wrench with a 1.1/2" Reducing Adaptor Stubby Screwdriver / Blow Mold Case

## No.T40M

# 40Pc. Metric Tap & Die Set High grade alloy steel

#### Taps & Dies

	3 X U.5MM			
	5 x 0.8mm	3 x 0.6mm	4 x 0.7mm	4 x 0.75mm
	7 x 0.75mm	5 x 0.9mm	6 x 0.75mm	6 x 1.0mm
þ	10 x 1.25mm	7 x 1.0mm	8 x 1.0mm	8 x 1.25mm
	1/8" x 27NPT	10 x 1.5mm	12 x 1.5mm	12 x 1.75mm
	"T" Style Tap Wre	ench / Bar Ty <sub>l</sub>	pe Tap Wrench	
	1" Dia. Die Stock	Wrench / Screw	Pitch Gauge	
	1/8"(3mm) Screw	driver / Blow M	fold Case	

### No.T40A

## 40Pc. SAE Tap & Die Set High grade alloy steel

		- C - Ingir grade a	noj oloon
Taps & Dies	6 x 32NC	8 x 32NC	10 x 24NC
4 x 36NS	12 x 24NC	1/4" x 20NC	1/4" x 28NF
10 x 32NF	5/16" x 24NF	3/8" x 16NC	3/8" x 24NF
5/16" x 18NC	7/16" x 20NF	1/2" x 13NC	1/2" x 20NF
7/16" x 14NC			
1/8" x 27NPT			

"T" Style Tap Wrench / Bar Type Tap Wrench 1" Dia. Die Stock Wrench / Screw Pitch Gauge 1/8"(3mm) Screwdriver / Blow Mold Case

## RETHREADING TOOLS



# **Rethreading-Tools**

#### TDT48 **Metric Stepped Tap Set**

Unique design stepped taps enable the eight most popular metric sizes in one small set. Made from high grade heat treated alloy steel.

Sizes: 3 x 0.5mm, 4 x 0.7mm 5 x 0.8mm, 6 x 1.0mm 7 x 1.0mm, 8 x 1.25mm 10 x 1.5mm, 12 x 1.75mm Supplied in plastic case.

#### TWTH2 1/4" T-Type Tap Wrench

Adjustable T-type tap wrench for use on small taps, reamers drills etc. with shanks from 1/8" to 1/4". Size: 1/8" to 1/4"(3 to 6mm)

#### 1/2" T-Type Tap Wrench TWTH4

Adjustable T-type tap wrench for use on medium taps, reamers drills etc. with shanks from 1/4" to 1/2". Size: 1/4" to 1/2"(6 to 13mm)

## 3/8" Bar-Type Tap Wrench

Adjustable bar-Type tap wrench for use on small taps, reamers drills etc. with shanks from 1/8" to 3/8". Size: 1/8" to 3/8"(3 to 10mm) Length: 8"(200mm)

#### TWBH5 1/2" Bar-Type Tap Wrench

Adjustable bar-Type tap wrench for use on medium taps, reamers drills etc. with shanks from 3/16" to 1/2". Size: 3/16" to 1/2"(5 to 13mm) Length: 10"(250mm)

#### TWBH6 3/4" Bar-Type Tap Wrench

Adjustable bar-Type tap wrench for use on large taps, reamers drills etc. with shanks from 1/4" to 3/4" Size: 1/4" to 3/4"(6 to 19mm) Length: 13.3/4"(350mm)

#### TWBH7 1" Bar-Type Tap Wrench

Adjustable bar-Type tap wrench for use on large

taps, reamers drills etc. with shanks from 3/8" to 1". Size: 3/8" to 1"(10 to 25mm) Length:17"(430mm)

#### TRS25 1"Round Die Stock

To suit 1"(25mm) button dies. Three adjusting screws provide secure fitting & adjustment to the selected die. Size: 1"(25mm) Length: 8"(200mm)

### TRS38 1.1/2"Round Die Stock

To suit 1.1/2"(38mm) button dies. Three adjusting screws provide secure fitting and adjustment to the selected die.

Size: 1.1/2"(38mm) Length: 13"(330mm)

### TRS50 2"Round Die Stock

To suit 2"(50mm) button dies. Three adjusting screws provide secure fitting and adjustment to the selected die.

Size: 2"(50mm) Length: 15.1/2"(390mm)





TWBH4



TWBH6












# **SOLDERING IRONS**







#### **Titanium Coated Drills S2 Steel Hex Bits**

# No.A8764 23 Pc Titanium Drill & Bit Set

#### **Drill Sizes:**

1.5mm, 2mm, 2.5mm, 3mm, 3.5mm, 4mm, 4.5mm, 5mm, 6mm, 8mm, 10mm #1, #2, #3 Phillips Bits x 30mm long #1, #2, #3 Pozi-Driv Bits x 30mm long 4mm, 6mm, 7.2mm Slotted Bits x 30mm long #2 Phillips & 7.2mm Slotted Bits x 58mm long 1/4"Hex Male x 1/4"Hex Female Bit Holder.





# No.8963 25mm HSS Stepped Drill

25mm high speed steel stepped drill has titanum coating and is hardened to HRC 62. Use on sheet metal to enlarge holes to required size.

**Stepped sizes:** 6mm, 9mm, 12mm, 14mm, 16mm, 17mm, 18mm, 19mm, 20mm, 22mm, 24mm, 25mm.

Shank size: 10mm



# No.8831 Jet Drill Kit

Only 4.1/2"(115mm) long, this handy pin vice handle with collet style chuck comes with 12 HSS wire gauge drills stored inside.

All the sizes you need to ream carburettor jets and any other job

with a small orifice. Casing handle is knurled for secure holding and has handy pocket clip. **Body length:**4.1/2"(115mm) **Drill sizes:** 

#52wg (.0635mm) #54wg (.0550mm) #56wg (.0465mm) #58wg (.0420mm) #60wg (.0400mm) #62wg (.0380mm) #64wg (.0360mm) #66wg (.0330mm) #68wg (.0310mm) #70wg (.0280mm) #72wg (.0250mm) #74wg (.0225mm)

# No.8830 Wire Gauge Cleaning Kit

For cleaning jets and tips on a multitude of applications. Storage compartment in the handle contains 12 colour coded 4"(100mm) knurled steel cleaning wires. Use the correct size

wire gauge numbered cleaner to reach hard to get at openings.

The handle features a built in steel chuck, handy pocket clip and all the sizes are imprinted on the casing with the corresponding colour identification. *Body length:*6"(150mm)

Sizes:

 Plain
 72 - 75wg (.025 - .021mm)
 Black
 70 - 71wg (.028 - .026mm)

 White
 68 - 69wg (.031 - .029mm)
 Maroon
 66 - 67wg (.033 - .032mm)

 Blue
 64 - 65wg (.036 - .035mm)
 Brown
 62 - 63wg (.038 - .037mm)

 Green
 60 - 61wg (.040 - .039mm)
 Red
 58 - 59wg (.042 - .041mm)

 Grey
 56 - 57wg (.046 - .043mm)
 Yellow
 54 - 55wg (.055 - .052mm)

 Orange
 52 - 53wg (.063 - .059mm)
 Purple
 49 - 51wg (.073 - .067mm)

# No.8835 Oxy-Tip Cleaner Set

Contains 13 wire gauge cleaners securely held in a flip-top aluminium case. Ideal for cleaning welding tips and other small orifices. Also includes a handy deburring file. Sizes: #52, #54, #56, #58,

**Sizes:** #52, #54, #56, #58, #60, #62, #64, #66, #68

#70, #72, #74, #76wg and Deburring file

#### Reams from 3 to 13mm

# No.8907 Tapered Reamer with Handle

Ream, deburr, align and enlarge holes.

Reamer is made of heat treated high grade tool steel for long life. To avoid damage tool must always be turned clockwise.

The use of cutting oil is recommended

Range: 1/8" to 1/2"(3 to 13mm)

#### Reams from 3 to 10mm

# No.8908 Small Tapered Reamer

Ream, deburr, align and enlarge holes.
T-handle makes turning easy. Reamer is made of heat treated high grade tool steel for long life. To avoid damage tool must always be turned clockwise.

The use of cutting oil is recommended Range: 1/8" to 3/8"(3 to 10mm)



# No.8909 Medium Tapered Reamer

Ream, deburr, align and enlarge holes.

T-handle makes turning easy. Reamer is made of heat treated high grade tool steel for long life.

To avoid damage tool must always be turned clockwise.

The use of cutting oil is recommended

Range: 1/8" to 1/2"(3 to 13mm)

# REAMERS, JET & TIP CLEANERS



Reams from 4 to 22mm

No.8910 **Large Tapered Reamer** 

Ream, deburr, align and enlarge holes.

T-handle makes turning easy. Reamer is made of heat treated high grade tool steel for long life.

To avoid damage tool must always be turned clockwise.

The use of cutting oil is recommended

Range: 5/32" to 7/8"(4 to 22mm)

Reams from 4 to 31mm

No.8911 **Extra Large Tapered Reamer** 

Ream, deburr, align and enlarge holes.

T-handle makes turning easy. Reamer is made of heat treated high grade tool steel for long life.

To avoid damage tool must always be turned clockwise.

The use of cutting oil is recommended

**Range:** 5/32" to 1.7/32"(4 to 31mm)







# No.8892 Mini Mechanic's Torch

Features high intensity beam from flood to spot with a twist of the wrist. Rugged machined aluminium construction with knurled design handle. Use with AAA cell battery. Spare long life globe inside cap. Length: 3.1/2"(90mm) *Diameter:* 7/8"(22mm)

No.8892-G Replacement globe for #8892



# No.8894 **Mechanic's Torch**

Features high intensity beam from flood to spot with a twist of the wrist. Rugged machined aluminium construction with knurled design handle. Works with our #8896 Fibre Optic Flexible Beam. Use with 2 x AA cell batteries. Spare long life globe inside cap.

Length: 5.3/4"(145mm) Diameter: 1"(25mm)

Replacement globe for #8894 No.8894-G



# No.8895 **Heavy-Duty Mechanic's Torch**

Features high intensity beam from flood to spot with a twist of the wrist. Rugged machined aluminium construction with knurled design handle. Use with 3 x D cell batteries. Spare long life globe inside cap Length: 13"(330mm) Diameter: 2.1/4"(57mm)

No.8895-G Replacement globe for #8895 No.8895-S Switch Assembly for #8895



8 LED Mechanics Torch

Features high intensity light beam. Rugged machined aluminum construction, with a on / off switch on the back.

Supplied with three AAA batteries. Includes vinyl carrying case. Length: 4"(100mm) **Diameter:** 1.1/16"(27mm)



# No.8896 **Fibre Optic Flex Torch Adaptor**

The flexible fibre optic shaft bends the high intensity beam around corners and into the most confined and obstructed areas. Adjust the intensity of the beam by rotating the head of the flashlight. Eliminates the problems of heat transfer and globe breakage as fibre optic tube emits high quality illumination with minimal visual obstruction or flood back. Works with T&E #8894 Torch and most AA flashlights.

Length: 7"(180mm) Head Cap Size: 1"(25mm)



No.8898-G Replacement LED Globe No.8898-B Replacement Battery Set No.8898-S Switch for #8898

# No.8898 **Magnetic Bend-A-Light**

High intensity super bright LED light with flexible stay-put shaft with magnets at both ends for inspections and retrieving small parts from normally inaccessible areas. Length:

17.1/2" (445mm)



Hands free flashlight: Two lights shine where you look. Can be worn with regular eye glasses. Perfect for working on vehicles, plumbing, electrical, etc. Lenses are adjustable to enable you to intensify the light onto the subject. Includes: 4 AAA batteries.

No.8891 Replacement Bulbs (2 per pack)





Bend-A-Light Torch With LED Flexible Stay-Put Adaptor Fitted





# No.8902 **LED & Ultra Violet Bend-A-Light Kit**

Three in one ultra thin Bend-A-Light kit includes: Super bright LED nozzle head and 400mm flexible stay-put adaptor. Ultra Violet nozzle head and 400mm flexible stay-put adaptor. Fiberoptic adaptor that works with LED and UV nozzles. Magnetic base to hold LED or UV light in position. AAA Battery pack included.

# No.8902LED **LED Bend-A-Light Kit**

Three in one ultra thin Bend-A-Light kit includes: Super bright LED nozzle head and 400mm flexible stay-put adaptor. Fiberoptic adaptor that works with LED and UV nozzles. Magnetic base to hold LED or UV light in position. AAA Battery pack included.

# No.8902UV **Ultra Violet Bend-A-Light Kit**

Three in one ultra thin Bend-A-Light kit includes: Ultra Violet nozzle head and 400mm flexible stay-put adaptor. Fiberoptic adaptor that works with LED and UV nozzles. Magnetic base to hold LED or UV light in position. AAA Battery pack included.



# **No.HR902** Retractable Reel Work Light

Workshop quality fluorescent work light with 30ft retractable oil resistant lead. Heavy duty unit comes complete with mounting kit, for easy car hoist or wall mount applications. Specifications: 240 volts / 12 amps / 9 watts No.HR903G Replacement 9w Fluoro. Tube



# **9Watt Fluorescent Lead Light** 12 Volt Powered

New strong durable work light. Features a clear lens on the end of the light for working in confined areas. Supplied with a wire hook attachment and battery clamp adaptors. Works on 12 volt DC power.

Light Dia.: 1.3/4"(45mm) Length: 12"(300mm)

Cable Length: 30ft(9m)

No.HR903-G Replacement Fluorescent Tube



#### HR2222K **Nut Set Rivet Kit**


Adjustment Device: Adjust one time, can work 1001 times.

Quick Change Mandrel: just plug and pull to change mandrel.

#### Thread Setting Sizes

modu Colling Cizor				
Rivet Size	M3	M4	M5	M6
Material	x0.5	x0.7	x0.8	x1.0
Aluminium Rivets Nut	•	•	•	•
Steel Rivets Nut	•	•	•	•
Stainless Rivets Nut	•	•	•	

Set contains 25 of each aluminium rivet nuts



Professional nut setting tool kit for securing threads on thin base metals. Giving extra strength to secure fasteners.



Set No. HR1K

#### HR1K Industrial Hand Riveter Kit

This high quality rivet gun has been constructed to give long life and robust performance. Its durable parts are heat treated to withstand continuous industrial use.

Supplied with four Interchangeable nozzles:

3/32", 1/8", 5/32", 3/16"(2.4mm,3.0/3.2mm,4mm,4.8/5.0mm) 20 pieces each 3/32", 1/8", 5/32", 3/16" Blind rivets.

Plastic carrying case.

Length: 10"(250mm)

Weight:	1.14lb(515g	)

Rivet Size	2.4mm	3.0/3.2mm	4.0mm	4.8/5.0mm
Rivet Material	3/32"	1/8"	5/32"	3/16"
Aluminium Rivets	•	•	•	•
Steel Rivets	•	•	•	•
Stainless Rivets	•	•	•	•

HR1-R Replacement Jaws to suit #HR1K Hand Rivet Gun

#### LT1 Lazy Tong Riveting Tool

Sets commercial rivets and structural rivets up to 1/4"(6.4mm) with five standard nose pieces. Robust and precise structure with high strength aluminium body, strong steel lattice, high grade alloy steel jaws and jaw case.

Forged alloy steel pins & bolts, core steel parts and comfortable handles with double bearings.

Long life operation. One year warranty.

Supplied with five standard Interchangeable nozzles:

1/8",5/32",3/16",6mm,1/4"(3.0/3.2mm,4.0mm,4.8/5mm,6mm,6.4mm)

Length Open:33"(830mm) Closed:12.5" (318mm)

Weight: 4.4lb(2kg)

Rivet size capacity for LT1 Lazy Tong Riveting Tool and LR1 Gear Type Lever Riveting Tool

Rivet Size	3.0/3.2mm	4.0mm	4.8/5.0mm	6.0mm	6.4mm
Rivet Material	1/8"	5/32"	3/16"		1/4"
Aluminium, Steel, Stainless					
Commercial Rivets				_	
Aluminium, Structural Rivets	•	•	•		•
Steel Structural Rivets	•	•	•		•

#### LT1-R Replacement Jaws to suit #LT1 & LR1 Riveting Tools

#### LR1 **Gear Type Lever Riveting Tool**

Sets commercial rivets and structural rivets up to 1/4"(6.4mm) with five standard nose pieces. Robust and precise structure with high strength aluminium body, high tension steel handles. Accurate & durable gear system, high grade alloy steel jaws and jaw case.

Wear resistant and torsion resistant Polygonal pivot pins with comfortable grips.

Long life operation. One year warranty.

Supplied with five standard Interchangeable nozzles:

1/8",5/32",3/16",6mm,1/4"(3.0/3.2mm,4.0mm,4.8/5mm,6mm,6.4mm)

Length: 24"(605mm) Weight: 4.3lb(1.95kg)

